

# A630 - A631 - A632

## 58 mm



2 YEAR WARRANTY



CLAMSHELL™



BLUETOOTH™



58 mm

### Key features

- Desktop (A630) / Portable (A631) / Automotive (A632)
- Compact design
- Long-lasting battery
- Built in Bluetooth™ (A631)



CHARACTERISTICS	UNIT	A630	A631	A632
Printing speed (max)	mm/s	55	50	55
Printing width	mm		48	
Resolution	dot/mm		8	
Number of dots	dot		384	
Number of columns	column		24 or 40	
Character size	dot*dot		9*24 or 16*24	
Resident code page	---		CP437	
Bar code type	---		UPC-A, UPC-E, JAN 8 (EAN 8), JAN 13 (EAN 13), code 39, 128, ITF	
Paper width	mm		58	
Paper roll diameter	mm		50	
Paper thickness	µm		Up to 80	
Paper loading	---		Clamshell™	
Operating voltage	VDC	9V	6V (NIMH battery)	12V
Current consumption	A		2.5	
Head pulse life	pulse		0.5*10 <sup>8</sup>	
Mechanical reliability	km		50	
Dimensions (W*D*H)	mm		108*147*72	
Weight	g	330 (printer only)	600 (printer+battery)	330 (printer only)
Operating temperature	°C/F		5 to 50/41 to 122	
Operating humidity	%RH		10 to 85	
Cutter	---		Manual tear bar	
Data buffer	Kbytes		4	
Flash Memory	Kbytes		64	
Interface	---	RS232/Centronics	RS232, Bluetooth™	RS232
Driver	---	Windows™ 98/00/XP	Windows™ 98/00/XP/Mobile	Windows™ 98/00/XP
Emulation	---		ESC/POS™	
CEM & Safety standards	---	UL/CAS60950, IEC/EN60950, CE Class B, FCC Class A, C-Tick	UL/CAS60950, IEC/EN60950, CE Class B, FCC Class A, C-Tick	E marking, UL/CAS60950 IEC/EN60950, CE Class B, FCC Class A, C-Tick
Added features	---	Desktop	Portable	Desktop
Accessories	---		Carrying Case	12 to 9V converter for car application